



深圳市新天源电子有限公司
Shenzhen XinTianYuan Electronics Co.,Ltd.

SPEC. NUMBER

PRODUCT GROUP
TFT-LCD

Rev.P0

ISSUE DATE
2024.11.05

PAGE
1 OF 13

3.95" LCM Product Specification Rev.P0

Customer	
Supplier	Shenzhen XinTianYuan Electronics Co.,Ltd.
Product name	3.95 Inch 总成
Model	TB039-I5008S45A-03

TITLE/SIGNATURE DATE

ITEM SIGNATURE DATE

Prepared heyong

Approved lixiyang



PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2024.11.05

SPEC. NUMBER

SPEC . TITLE
3.95 LCM+CTP Product Specification

PAGE
2 OF 13

REVISION HISTORY

[illegible]



PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2024.11.05

SPEC. NUMBER

SPEC. TITLE

3.95 LCM+CTP Product Specification

PAGE

3 OF 13

Contents

- 1. GENERAL INFO RMATION 主要特征描述
- 2. ELECTRICAL CHARACTERISTICS 电气参数
 - 2.1 LCM Electrical Characteristics 模组电气参数
- 3. EXTERNAL DIMENSIONS AND INTERFACE DESCRIPTION 外形接口定义
 - 3.1 External Dimensions 外形尺寸
 - 3.2 LCM interface description LCM 接口功能描述
 - 3.3 TP interface description TP 接口功能描述
 - 3.4 Power on/off sequence 上下电时序描述
 - 3.5 RGB Interface Definition 屏参描述
- 4. ELECTRO-OPTICAL CHARACTERISTICS 光电参数
 - 4.1 LCM ELECTRO_Optical Characteristics LCM 光电参数
- 5. RELIABILITY TEST CONDITIONS 可靠性试验条件

	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2024.11.05
SPEC. NUMBER	SPEC. TITLE 3.95 LCM+CTP Product Specification		PAGE 4 OF 13

1. GENERAL INFORMATION主要特征描述

Item of general information 项目	Contents 内容	Unit 单位
LCD Type 液晶显示类型	TFT/TRANSMISSIVE	/
Recommended Viewing Direction 模块推荐使用方向	ALL	O' Clock
Module area (W×H×T) 模块外围尺寸(宽×高×厚)	84(W)*84(L)*2.88(H)	mm
Active area (W×H) 有效区域 (宽×高)	71.86(W)*70.18(L)	mm
Number of Dots 点阵	480(RGB)×480	/
Pixel pitch (W×H) 像素大小(宽×高)	0.0502×0.1432	mm
Driver IC 驱动IC	TBD	/
Interface Type 接口类型	RGB	/
Colors 色彩	16.7M	/
Backlight Type 背光类型	LED	/

2. Electrical Characteristics 电气参数

2.1 LCM Electrical Characteristics 模组电气参数

2.1.1. ABSOLUTE MAXIMUM RATINGS 极限参数

Parameter of absolute maximum ratings 参数	Symbol 符号	Min 最小值	Max 最大值	Unit 单位
Operating temperature 操作温度	T _{op}	-10	60	℃
Storage temperature 储存温度	T _{st}	-20	70	℃
Humidity 湿度	RH	-	90%(Max60 ℃)	RH

2.1.2. ELECTRICAL CHARACTERISTICS 模块电气特性

Parameter of DC characteristics 参数	Symbol 符号	Min 最小值	Typ 典型值	Max 最大值	Unit 单位
Analog power supply voltage 模拟电源电压	VCI	3.0	3.3	3.6	V
I/O power supply 接口电压	/	/	/	/	V
Input Current 输入电流	I _{dd}	-	45		mA
Input voltage 'H' level 输入高电平	V _{IH}	0.7VCC	-	VCC	V
Input voltage 'L' level 输入低电平	V _{IL}	VSSI	-	0.3VCC	V



PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2024.11.05

SPEC. NUMBER

SPEC. TITLE

3.95 LCM+CTP Product Specification

PAGE


5 OF 13

2.1.3. Backlight Characteristics 背光电气特性

Item of backlight characteristics 项目	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward voltage 正向电压	V_f	12	12.4	12.8	V	$I_f=40\text{mA}$
Number of LED LED数量	-	-	8	-	Piece	-
Connection mode 连接类型	4S2P	-		-	-	-

Using condition: constant current driving method $I_f=40\text{mA}$ (+/-10%).

使用条件：恒流的驱动方式 $I_f=40\text{mA}$ (+/-10%).



LED CIRCUIT DIAGRAM

($I_f=40\text{mA}$, $V_f=12\text{V}-12.8\text{V}$)

Backlight LED Circuit



PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2024.11.05

SPEC. NUMBER

SPEC. TITLE

3.95 LCM+CTP Product Specification

PAGE

7 OF 13

3.2 LCM interface description LCM接口功能描述

PIN	DESC	Function
1	GND	Power Ground
2	TP- INT	Touch screen interrupt
3	TP-SCL	I2C interface clock pin
4	TP-SDA	I2C interface data pin
5	TP-RESET	External reset for TP
6	GND	Ground
7	SDA	RGB input data Pin
8	SCL	RGB CLK Pin
9	CS	RGB Chip select pin.
10	RESET	Global reset signal. Low active.
11	SD0	Input or output data Pin
12	GND	Ground
13	VCI	Input Voltage+3.3V
14	VCI	Input Voltage+3.3V
15	R7	Red data
16	R6	Red data
17	R5	Red data
18	R4	Red data
19	R3	Red data
20	R2	Red data
21	R1	Red data
22	R0	Red data
23	G7	Green data
24	G6	Green data
25	G5	Green data
26	G4	Green data
27	G3	Green data
28	G2	Green data
29	G1	Green data
30	G0	Green data
31	B7	Blue data
32	B6	Blue data
33	B5	Blue data
34	B4	Blue data
35	B3	Blue data
36	B2	Blue data
37	B1	Blue data
38	B0	Blue data
39	GND	Power Ground
40	DE	Data enable signal in RGB interface.
41	PCLK	Dot clock signal in RGB interface. (DOTCLK)
42	HS	Horizontal (Line) synchronizing input signal in RGB interface.
43	VS	Vertical (Frame) synchronizing input signal in RGB interface.
44	GND	Ground
45	LED-A	Power for LED backlight(anode)
46	LED-A	Power for LED backlight(anode)
47	LED-K	Power for LED backlight(Cathode)
48	LED-K	Power for LED backlight(Cathode)
49	GND	Ground
50	GND	Ground



PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2024.11.05

SPEC. NUMBER

SPEC. TITLE


3.95 LCM+CTP Product Specification

PAGE

8 OF 13

3.4 Power on/off sequence.

The power on/off sequence is illustrated below



Power on/off sequence timing

	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2024.11.05
SPEC. NUMBER	SPEC. TITLE 3.95 LCM+CTP Product Specification		PAGE 9 OF 13

3.5. RGB Interface Definition

Horizontal Timing

Parameter	Symbol	Spec.			Unit
		Min.	Typ.	Max.	
DCLK Frequency	fclk	-	18	-	MHz
Horizontal Display Area	thd	480			DCLK
HS Period	th		590	-	DCLK
HS Pulse Width	thpw	-	20	-	DCLK
HS Back Porch	thbp	-	20	-	DCLK
HS Front Porch	thfp	-	70	-	DCLK

Vertical Timing

Parameter	Symbol	Spec.			Unit
		Min.	Typ.	Max.	
Vertical Display Area	tvd	480			TH
VS Period	tv	-	508	-	TH
VS Pulse Width	tvpw	-	2	-	TH
VS Back Porch	tvbp		12		TH
VS Front Porch	tvfp	-	14	-	TH

	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2024.11.05
SPEC. NUMBER	SPEC. TITLE 3.95 LCM+CTP Product Specification		PAGE 10 OF 13

4. ELECTRO-OPTICAL CHARACTERISTICS 光电参数

4.1 LCM ELECTRO_Optical Characteristics LCM光电参数

Item of electro-optical characteristics 项目	Symbol 符号	Condition 条件	Min 最小值	Typ 典型值	Max 最大值	Unit 单位	Remark 注释
Contrast ratio 对比度	CR	$\theta = 0^{\circ}$ $\psi = 0^{\circ}$ $I_f = 20\text{mA}$ /LED	1000	1200	-	-	Note 1
SurfaceLuminance 表面亮度	Lv		-	350	-	Cd/m ²	Note 2
Luminance uniformity 均匀度	δ (WHITE)		75	-	-	%	Note 3
Response time 响应时间	Tr+Tf		-	30	35	ms	Note 4
Viewing angle range 视角范围	θ (CR ≥ 10)	6o' clock	70	80	-	degree	Note 5
		12o' clock	70	80	-		
		3o' clock	70	80	-		
		9o' clock	70	80	-		
Module Chromaticity CIE (x, y) 色坐标	White	x	0.265	0.285	0.315	-	Note6
		y	0.260	0.280	0.310		
NTSC Ratio 色域	S	-	-	70	-	%	Note7

Note1. Contrast Ratio (CR) is defined mathematically by the following formula. For more information see FIG 1.:

Contrast Ratio = $\frac{\text{Average Surface Luminance with all white pixels (P1, P2, P3, P4,P5,P6,P7,P8,P9)}}{\text{Average Surface Luminance with all black pixels (P1, P2, P3, P4,P5,P6,P7,P8,P9)}}$

备注1. 对比度是由以下公式计算所得。详见FIG 1.。

对比度 = $\frac{\text{显示白色画面时平均表面亮度(P1,P2,P3,P4,P5,P6,P7,P8,P9)}}{\text{显示黑色画面时平均表面亮度(P1,P2,P3,P4, P5,P6,P7,P8,P9)}}$

Note2. Surface brightness is the center brightness value of the test when displaying a white screen. For more information see FIG 1.

Lv = Surface Luminance with center pixels (P5)

备注2. 表面亮度是在显示白色画面时，测试的中心亮度值，详见FIG 1.。

Lv = 中心点表面亮度(P5)

Note3. The uniformity in surface luminance (δ WHITE) is determined by measuring luminance at each test

	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2024.11.05
SPEC. NUMBER	SPEC. TITLE 3.95 LCM+CTP Product Specification	PAGE 11 OF 13	

position 1 through 9, and then dividing the maximum luminance of 9 points luminance by minimum luminance of 9 points luminance. For more information see FIG 1.

$$\delta \text{ WHITE} = \frac{\text{Minimum Surface Luminance with all white pixels (P1, P2,P3,P4,P5,P6,P7,P8,P9)}}{\text{Maximum Surface Luminance with all white pixels (P1, P2,P3,P4,P5,P6,P7,P8,P9)}}$$

备注3. 均匀度是在显示白色画面时，测试P1到P9的亮度，然后再用5个点亮度的最小值除以最大值。详见 FIG 1. 。

$$\text{均匀度} = \frac{\text{表面亮度最小值(P1, P2, P 3,P4, P5,P6,P7,P8,P9)}}{\text{表面亮度最大值(P1, P2, P 3,P4, P5,P6,P7,P8,P9)}}$$

Note4. Response time is the time required for the display to transition from White to black(Rise Time, Tr) and from black to white(Decay Time, Tf). For additional information see FIG 2..

备注4. 响应时间是Tr(上升时间)与Tf(下降时间)的和; Tr 指显示黑色画面转为显示白色画面需要时间, Tf 指显示白色画面转为显示黑色画面需要时间。详见FIG 2. 。

Note5. Viewing angle is the angle at which the contrast ratio is greater than 2. For TFT module the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 3.

备注5. 视角指对比度大于等于2时的可视范围，对TFT 屏，则是对比度大于等于10 的可视范围。视角由横轴（x轴），竖轴（y轴）同Z轴(垂直于LCD 表面)之间的夹角来定义。详见FIG 3.

Note6. CIE (x, y) chromaticity ,The x,y value is determined by screen active area position 5. For more information see FIG 1.

备注6. CIE(x,y) 色坐标测试点为显示屏中心点P5。详见FIG 1.

Note7: NTSC ratio: For more information see FIG 4.

$$\text{NTSC ratio} = \frac{\text{Area of RGB triangle}}{\text{Area of NTSC triangle}}$$

备注7. 色域比： 详见FIG 4

$$\text{NTSC ratio} = \frac{\text{RGB三色三角形面积}}{\text{标准NTSC三角形面积}}$$

Note8. For Viewing angle and response time testing, the testing data is base on Autronic-Melchers’s ConoScope. Series Instruments. For contrast ratio, Surface Luminance, Luminance uniformity and CIE, the testing data is base on BM-7 photo detector.


备注8. 视角和响应时间， 测试数据基于Autronic-Melchers’s ConoScope. 系列。而对比度，表面亮度，均匀度，CIE 坐标, 测试数据基于BM-7 photo detector.

Note9. For TFT transmissive module, Gray scale reverse occurs in the direction of panel viewing angle

备注9. TFT 全透产品,在视角方向会发生灰度反转

FIG. 1. Measuring method for Contrast ratio,surface luminance, Luminance uniformity,CIE (x, y) chromaticity对比度，表面亮度，均匀度，CIE坐标测试方法

A :H/6 mm
B : V/6 mm
Active Area
spot size Ø=5mm, 500mm distance from the surface to detector lens
measurement instrument is luminance meter BM-7



	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2024.11.05
SPEC. NUMBER	SPEC. TITLE 3.95 LCM+CTP Product Specification		PAGE 12 OF 13

FIG. 2. The definition of Response Time 响应时间定义




FIG.3. The definition of viewing angle 视角定义





Fig.4. 1931 CIE chromaticity diagram

	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2024.11.05
SPEC. NUMBER	SPEC. TITLE 3.95 LCM+CTP Product Specification		PAGE 13 OF 13

5. RELIABILITY TEST CONDITIONS 可靠性试验条件

No. 序号	Test Item 试验项目	Test Condition 试验条件	Inspection after test 判断标准
1	High Temperature Storage 高温存放	70±2℃/96 hours	Inspection after 2~4hours storage at room temperature, the sample shall be free from defects: 试验结束后, 已测试的LCD 样品必须在室内正常温湿度环境下放置2~4 个小时以上才能进行功能和外观检查, 样品不允许有以下缺陷: 1.Air bubble in the LCD; 模块中有气泡 ; 2.Sealleak; 封口松脱; 3.Non-display; 不显示; 4.missing segments; 漏笔 5.Glass crack; 玻璃破碎; 6.Current Idd is twice higher than initial value. 电流Idd 大于初时值的2 倍 7, the surface shall be free from damage. 表面无损伤. 8. The electrical characteristics requirements shall be satisfied. 需要满足模块电气性能。
2	Low Temperature Storage 低温存放	-20±2℃/96 hours	
3	High Temperature Operating 高温操作	60±2℃/96 hours	
4	Low Temperature Operating 低温操作	-10±2℃/48 hours	
5	Temperature Cycle 冷热循环	-10±2℃(30min.) ~60(30min.)±2℃×48 cycles	
6	High temperature and high humidity 高温高湿	60℃±5℃×90%RH/48 hours	
7	Vibration Test 振荡试验	Frequency: 10Hz~55Hz~10Hz Amplitude: 1.5mm, X, Y, Zdirection for total 0.5hours (Packing condition)	
8	Dropping test 跌落试验	Drop to the ground from 1.0m height, one time, every side of carton. (Packing condition)	
9	ESD test 静电试验	R: 330Ω C: 150pF , 10time Air discharge: ±6KV Contact discharge: ±4KV	

Remark: 注意:

1. The test samples should be applied to only one test item. 每个被测试的模块只能用于其中的一个测试项目。

2. Sample size for each test item is 5~10pcs. 每个测试项目的样品数量为5~10 片。

3. For Damp Proof Test, Pure water(Resistance > 10MΩ) should be used. 对于防潮试验, 试验箱的用水必须是电阻大于10M 欧姆的纯水。

4. In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judged as a good part. 如果由静电引起产品故障, 当放置一段时间后能够恢复正常, 则不视为产品缺陷。

5. EL evaluation should be excepted from reliability test with humidity and temperature: Some defects such as black spot/blemish can happen by natural chemical reaction with humidity and Fluorescence EL has. 带EL片的可靠性测试在高温高湿条件下, 荧光粉会发生自然化学反应而产生黑点或瑕疵, 因此不在高温高湿条件测试范围内。

6. Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic. 故障判断标准:基本规格, 电气特性, 机械特性, 光电特性